

SmartLam GL19C

Higher stiffness means
a more compact section.



SmartLam GL19C substitution tables

65mm ➔ 60mm		85mm ➔ 75mm	
GL17C	SmartLam GL19C	GL17C	SmartLam GL19C
130 x 65 ➔	130 x 60	130 x 85 ➔	130 x 75
165 x 65 ➔	165 x 60	165 x 85 ➔	165 x 75
195 x 65 ➔	195 x 60	195 x 85 ➔	195 x 75
230 x 65 ➔	230 x 60	230 x 85 ➔	230 x 75
260 x 65 ➔	260 x 60	260 x 85 ➔	260 x 75
295 x 65 ➔	295 x 60	295 x 85 ➔	295 x 75
330 x 65 ➔	330 x 60	330 x 85 ➔	330 x 75
360 x 65 ➔	360 x 60	360 x 85 ➔	360 x 75

- AS/NZ 1328 Appearance grade B, sanded faces - suits painted applications
- Stiffness E 19,000 MPa, Bending (f_b) - 45 MPa, JD2
- Available in H2
- Pre-cambered



www.tilling.com.au
Sales 1800 33 77 03
Technical 1300 66 86 90



The information contained in this product document is current as at May 2021 and is based on data available to Tilling Timber Pty Ltd at the time of going to print. Tilling Timber Pty Ltd has used its reasonable endeavours to ensure the accuracy and reliability of the information contained in this document and, to the extent permitted by law, will not be liable for any inaccuracies, omissions or errors in this information nor for any actions taken in reliance on this information. Tilling Timber Pty Ltd reserves the right to change the information contained in this document without prior notice. It is important that you call the Tech Support customer Helpline on 1300 668 690 to confirm that you have the most up to date information available.

© 2021 Tilling Timber Pty Ltd ABN 92 004 621 121 Date of publication May 2021 SmartFrame is a Registered Trademark of Tilling Timber