

## MULTIBOND SMX25 – FLEX & SEAL



### DESCRIPTION

Multibond SMX25 is a high quality, low modulus, single component, permanently highly flexible joint sealant with higher viscosity. Perfect for internal & external applications. Based on SMX® Polymer SMX25 has a "Shore A" hardness of 25 and can accommodate movement of  $\pm 25\%$ . SMX25 has excellent UV resistance, elasticity and can be sanded and painted with most types of paint. Once cured forms a strong, flexible, waterproof seal and bonds to the widest range of substrates. SMX25 can be used for damp surfaces.

### APPLICATIONS

Multibond SMX25 – Flex & Seal is ideal for a wide range of sealing applications in construction and industry including.....

- Expansion joints
- Joints under waterproofing membranes (water-based, solvent-based and acrylic)
- Masonry and precast concrete joints
- For sanitary, bathroom and kitchen areas (resists mould growth)
- For walls and perimeter joints
- For lap joints in roofing, guttering and cladding,
- For air conditioning ducting,
- For caravan, bus and automotive use
- For window and door frames

### FEATURES & BENEFITS

- Low modulus
- Higher viscosity
- **Highly flexible  $\pm 25\%$**
- Internal & external
- UV resistant



Colour		Size	Item Code
Concrete Grey		600ml	130252
White		600ml	130248
Black		600ml	130254
Beige		600ml	130250
Dark Grey		600ml	130249
Sandstone		600ml	130253
Off White		600ml	130251

### Similar products in the industry





## MULTIBOND SMX35 – SEAL & STRETCH



### DESCRIPTION

Multibond SMX35 is a high quality, single component, permanently flexible joint sealant. Perfect for internal & external applications. Based on SMX® Polymer Multibond SMX35 has a "Shore A" hardness of 35 and can accommodate movement of  $\pm 20\%$ . Multibond SMX35 has excellent UV resistance, elasticity and can be sanded and painted with most types of paint. Once cured forms a strong, flexible, waterproof seal and bonds to the widest range of substrates. Multibond SMX35 can be used for damp surfaces.

### APPLICATIONS

Multibond SMX35 - Seal & Stretch is ideal for a wide range of sealing applications in construction and industrial including...

- Expansion joints
- Joints under waterproofing membranes (water-based, solvent-based and acrylic)
- Masonry and precast concrete joints
- For sanitary, bathroom and kitchen areas (resists mould growth)
- For walls and perimeter joints
- For water retaining structures (Concrete Grey water potable approved)
- For lap joints in roofing, guttering and cladding,
- For air conditioning ducting,
- For caravan, bus and automotive use
- For window and door frames



### FEATURES & BENEFITS

- Elastic sealant
- Highly flexible  $\pm 20\%$
- Internal & external
- **Easy to gun**
- UV Resistant

### Similar products in the industry



Colour		Size	Item Code
Concrete Grey		290ml 600ml	124605 124618
White		290ml 600ml	124604 124598
Black		290ml 600ml	124620 124619
Beige		600ml	124789
Dark Grey		600ml	124790
Sandstone		600ml	124787
Off White		600ml	124788



## MULTIBOND SMX50 – SEAL & STICK



### DESCRIPTION

Multibond SMX50 is a high quality, fast curing, single component flexible adhesive and sealant with high adhesive strength. Perfect for internal & external applications. Based on SMX® Polymer Multibond SMX50 has a “Shore A” hardness of 40 ideal for trafficable joints and can accommodate movement of ± 20%. Multibond SMX50 has excellent UV resistance, elasticity and can be sanded and painted with most types of paint. Once cured forms a strong, flexible, waterproof seal and bonds to the widest range of substrates. Multibond SMX50 can be used for damp surfaces.

### APPLICATIONS

Multibond SMX50 is ideal for a wide range of bonding and sealing applications in construction and industrial including.....

- For trafficable expansion joints
- For trafficable pavement floors and perimeter joints,
- Joints under waterproofing membranes (water-based, solvent-based and acrylic)
- For sanitary, bathroom and kitchen areas (resists mould growth)
- For lap joints in roofing, guttering and cladding
- For air conditioning ducting
- For caravan, bus, automotive use

### FEATURES & BENEFITS

- Fast curing
- Sealing & bonding
- Internal & external
- **Trafficable**
- UV Resistant



Colour		Size	Item Code
Concrete Grey		290ml	128737
		600ml	124542
White		290ml	128738
		600ml	124617
Black		290ml	128736
		600ml	124606

### Similar products in the industry



Bostik Seal'N Flex FC

Sikaflex 11FC

Fuller Superseal HPR50FC

Fuller Toolbox / Maxfix

Bostik Xtreme Fix

Parchem Emer-seal PU40