



2C ADHESIVE

DESCRIPTION

2C Adhesive is a two pack system consisting of a high viscosity cyanoacrylate adhesive and an aerosol activator.

APPLICATIONS

- Bonding of wooden mitre joints
- Fixing and repairing wooden parts
- Suitable for the fast bonding of e.g. MDF, plastics, metal, timber, porcelain, cork, leather, ceramics, cardboard, paper and rubber.

FEATURES & BENEFITS

- High bond strength
- Very fast bonding
- Suitable for use on vertical surfaces as it will not drip or slump.



Technical Data - Adhesive	
Basis	Cyano acrylate
Consistency	Liquid gel
Curing system	Chemical curing
Density	1.06 g/mL
Viscosity	1200 - 1800 cps at 25 °C
Flash point	>81 °C
Temperature resistance	-20 °C to 70 °C
Application temperature	5 °C to 35 °C

Colour	Size	Units / Box	Bar Code	Item Code
Transparent <input type="checkbox"/>	50 g adhesive 200 mL activator	30	5411183115309	135623
	100 g adhesive 400 mL activator	24	5411183115323	135624

Technical Data - Activator	
Basis	Hexane
Consistency	Liquid
Temperature resistance	-20 °C to 70 °C
Application temperature	5 °C to 35 °C

